

WEST LAKE
TIRES

2026 PRODUCT CATALOG



PRODUCT LINEUP



FORAY RP218

TOURING · PASSENGER CAR

- 64 Sizes
- 13" - 19" Rim Diameters
- Road Hazard Program
- ~10/32 Tread Depth
- 55K Limited Treadwear Warranty
- T, H, & V Speed Rated



SA07 SPORT

PERFORMANCE TOURING · PASSENGER CAR

- 69 Sizes
- 16" - 22" Rim Diameters
- Road Hazard Program
- 10/32 Tread Depth
- 45K Limited Treadwear Warranty
- V, W, & Y Speed Rated



SU318 RADIAL H/T

TOURING · CUV / SUV

- 46 Sizes
- 15" - 22" Rim Diameters
- Road Hazard Program
- ~12/32 Tread Depth
- 50K Limited Treadwear Warranty
- T, H, & V Speed Rated



SL309 RADIAL A/P

A/P · LIGHT TRUCK

- 10 Sizes
- 16" - 18" Rim Diameters
- Road Hazard Program
- 40K Limited Treadwear Warranty
- Q Speed Rated



SL369 RADIAL A/T

A/T · LIGHT TRUCK

- 45 Sizes
- 15" - 20" Rim Diameters
- Road Hazard Program
- 40K Limited Treadwear Warranty
- Q, R, S, & T Speed Rated



SL376 RADIAL M/T

M/T · LIGHT TRUCK

- 27 Sizes
- 15" - 26" Rim Diameters
- Q & R Speed Rated



SC328

COMMERCIAL · VAN

- 1 Size
- 16" Rim Diameter



CONTENTS

FORAY RP218	02
SA07 SPORT	04
SU318 RADIAL H/T	06
SL309 RADIAL A/P	08
SL369 RADIAL A/T	10
SL376 RADIAL M/T	12
SC328 COMMERCIAL VAN	14
SIZE MATRIX	16
WARRANTY INFORMATION	18

FORAY RP218

TOURING · PASSENGER CAR

QUICK FACTS

- 64 Sizes · 13" - 19" Rim Diameters · Touring
- ~10/32 Tread Depth · Limited Treadwear Warranty



55K
MILE WARRANTY



ROAD HAZARD
PROGRAM

T.H.V
SPEED RATING

600/540 A A
UTQG

The **RP218** is designed to provide an outstanding driving experience at a remarkable value, no matter where the road takes you. With its modern all-season touring tread design, the RP218 delivers reliable performance and a smooth, comfortable ride you can trust year-round. Wide circumferential grooves aid in reducing hydroplaning while improving overall control and the RP218's lateral and angled grooves evacuate water to increase wet traction. The RP218 uses angled notches to provide additional traction and to improve the overall tread life, while the angled variable depth siping delivers enhanced handling and traction.



REDUCED NOISE



WET TRACTION



ALL-SEASON



WIDE CIRCUMFERENTIAL GROOVES

Aid in reducing hydroplaning and improve control.



LATERAL AND ANGLED GROOVES

Evacuates water and increases wet traction.



ANGLED VARIABLE DEPTH SIPING

Delivers enhanced handling and traction.



ANGLED NOTCHES

Help improve the overall tread life while providing additional traction.



Wheel Diameter	Size	Item Number	Service Index	Sidewall	LR/PR	Tread Depth	Rim Width (Measured)	Rim Width (Approved)	Section Width	Overall Diameter	Max Load	Approximate Weight	UTQG
13"	155/80R13	24000091	79T	BW	SL	9/32	4.50	4.00 - 5.00	6.2	22.8	963@44	13.3	500 A A
	175/70R13	24000092	82T	BW	SL	9/32	5.00	4.50 - 6.00	7.0	22.7	1047@44	14.2	500 A A
	175/65R14	24000097	82H	BW	SL	9/32	5.00	5.00 - 6.00	7.0	23.0	1047@44	15.1	500 A A
14"	175/70R14	24000093	84T	BW	SL	9/32	5.00	4.50 - 6.00	7.0	23.7	1102@44	15.0	500 A A
	185/60R14	24000099	82H	BW	SL	9/32	5.50	5.00 - 6.50	7.4	22.8	1047@44	15.4	500 A A
	185/65R14	24000098	86H	BW	SL	9/32	5.50	5.00 - 6.50	7.4	23.5	1168@44	16.1	500 A A
	185/70R14	24000094	88T	BW	SL	9/32	5.50	4.50 - 6.00	7.4	24.3	1235@44	16.6	500 A A
	195/70R14	24000095	91H	BW	SL	10/32	5.00	5.00 - 6.50	7.9	24.8	1356@44	18.2	540 A A
	205/70R14	24000096	98T	BW	XL	10/32	6.00	5.00 - 7.00	8.2	25.4	1653@51	20.7	540 A A
	175/65R15	24000102	84V	BW	SL	9/32	5.00	5.00 - 6.00	7.0	24.0	1102@44	16.1	500 A A
15"	185/55R15	24000111	82V	BW	SL	9/32	6.00	5.00 - 6.50	7.6	23.0	1047@44	16.4	500 A A
	185/60R15	24000107	84H	BW	SL	10/32	5.50	5.00 - 6.50	7.4	23.7	1102@44	17.0	540 A A
	185/65R15	24000103	88H	BW	SL	10/32	5.50	5.00 - 6.50	7.4	24.4	1235@44	17.7	540 A A
	195/50R15	24000113	82V	BW	SL	10/32	6.00	5.50 - 7.00	7.9	22.7	1047@44	16.7	540 A A
	195/55R15	24000112	85V	BW	SL	10/32	6.00	5.50 - 7.00	7.9	23.4	1135@44	17.6	540 A A
	195/60R15	24000108	88V	BW	SL	10/32	6.00	5.50 - 7.00	7.9	24.2	1235@44	17.8	540 A A
	195/65R15	24000104	91H	BW	SL	10/32	6.00	5.50 - 7.00	7.9	25.0	1356@44	19.1	540 A A
	205/60R15	24000109	91H	BW	SL	10/32	6.00	5.50 - 7.50	8.2	24.7	1356@44	19.2	540 A A
	205/65R15	24000105	94H	BW	SL	10/32	6.00	5.50 - 7.50	8.2	25.5	1477@44	19.9	540 A A
	205/70R15	24000100	96T	BW	SL	10/32	6.00	5.00 - 7.00	8.2	26.3	1565@44	22.4	540 A A
	215/60R15	24000110	94H	BW	SL	10/32	6.50	6.00 - 7.50	8.7	25.2	1477@44	21.6	540 A A
	215/65R15	24000106	96H	BW	SL	10/32	6.50	6.00 - 7.50	8.7	26.0	1565@44	22.7	540 A A
	215/70R15	24000101	98H	BW	SL	10/32	6.50	5.50 - 7.00	8.7	26.9	1653@44	23.7	540 A A
	185/55R16	24000122	83V	BW	SL	9/32	6.00	5.00 - 6.50	7.6	24.0	1074@44	16.9	500 A A
	195/50R16	24000125	84V	BW	SL	10/32	6.00	5.50 - 7.00	7.9	23.7	1102@44	17.6	540 A A
195/55R16	24000123	87V	BW	SL	10/32	6.00	5.50 - 7.00	7.9	24.4	1201@44	18.6	540 A A	
205/50R16	24000126	87V	BW	SL	10/32	6.50	5.50 - 7.50	8.4	24.1	1201@44	19.9	540 A A	
205/55R16	24000124	91V	BW	SL	10/32	6.50	5.50 - 7.50	8.4	24.9	1356@44	19.9	540 A A	
205/60R16	24000118	92V	BW	SL	10/32	6.00	5.50 - 7.50	8.2	25.7	1389@44	19.9	540 A A	
205/65R16	24000114	95H	BW	SL	10/32	6.00	5.50 - 7.50	8.2	26.5	1521@44	22.7	540 A A	
205/70R16	24000154	97T	BW	SL	10/32	6.00	5.00 - 7.00	8.2	27.3	1609@44	22.8	540 A A	
215/55R16	24000127	97H	BW	XL	10/32	7.00	6.00 - 7.50	8.9	25.3	1609@51	21.3	540 A A	
215/60R16	24000119	95V	BW	SL	10/32	6.50	6.00 - 7.50	8.7	26.1	1521@44	22.5	540 A A	
215/65R16	24000115	102V	BW	XL	10/32	6.50	6.00 - 7.50	8.7	27.0	1874@51	24.2	540 A A	
215/70R16	24000139	100H	BW	SL	10/32	6.50	5.50 - 7.00	8.7	27.9	1764@44	25.3	540 A A	
225/55R16	24000128	99V	BW	XL	10/32	7.00	6.00 - 8.00	9.2	25.7	1709@51	23.8	540 A A	
225/60R16	24000120	98V	BW	SL	10/32	6.50	6.00 - 8.00	9.0	26.6	1653@44	23.7	540 A A	
225/65R16	24000116	100H	BW	SL	10/32	6.50	6.00 - 8.00	9.0	27.5	1764@44	26.0	540 A A	
225/70R16	24000140	103H	BW	SL	10/32	6.50	6.00 - 7.00	9.0	28.4	1929@44	26.3	540 A A	
235/60R16	24000121	100H	BW	SL	10/32	7.00	6.50 - 8.50	9.4	27.1	1764@44	26.0	600 A A	
235/65R16	24000117	103H	BW	SL	10/32	7.00	6.50 - 8.50	9.4	28.0	1929@44	27.3	600 A A	
205/50R17	24000132	93V	BW	XL	10/32	6.50	5.50 - 7.50	8.4	25.1	1433@51	21.8	600 A A	
215/50R17	24000133	95V	BW	XL	10/32	7.00	6.00 - 7.50	8.9	25.5	1521@51	22.5	600 A A	
215/55R17	24000129	94V	BW	SL	10/32	7.00	6.00 - 7.50	8.9	26.3	1477@44	22.6	600 A A	
215/60R17	24000144	100V	BW	XL	10/32	6.50	6.00 - 7.50	8.7	27.2	1764@51	24.3	600 A A	
215/65R17	24000141	99H	BW	SL	10/32	6.50	6.00 - 7.50	8.7	28.0	1709@44	25.7	600 A A	
225/50R17	24000134	94V	BW	SL	10/32	7.00	6.00 - 8.00	9.2	25.9	1477@44	23.1	600 A A	
225/55R17	24000130	101V	BW	XL	10/32	7.00	6.00 - 8.00	9.2	26.8	1879@51	25.6	600 A A	
225/60R17	24000145	99V	BW	SL	10/32	6.50	6.00 - 8.00	9.0	27.6	1709@44	25.6	600 A A	
225/65R17	24000142	102H	BW	SL	10/32	6.50	6.00 - 8.00	9.0	28.5	1874@44	26.9	600 A A	
235/50R17	24000135	96V	BW	SL	10/32	7.50	6.50 - 8.50	9.6	26.3	1565@44	25.0	600 A A	
235/55R17	24000131	99V	BW	SL	10/32	7.50	6.50 - 8.50	9.6	27.2	1709@44	26.6	600 A A	
235/60R17	24000146	102H	BW	SL	10/32	7.00	6.50 - 8.50	9.4	28.1	1874@44	27.4	600 A A	
235/65R17	24000143	108H	BW	XL	10/32	7.00	6.50 - 8.50	9.4	29.1	2205@51	29.7	600 A A	
225/50R18	24000137	95V	BW	SL	10/32	7.00	6.00 - 8.00	9.2	26.9	1521@44	25.3	600 A A	
225/55R18	24000136	98V	BW	SL	10/32	7.00	6.00 - 8.00	9.2	27.8	1653@44	24.5	600 A A	
225/60R18	24000147	104H	BW	XL	10/32	6.50	6.00 - 8.00	9.0	28.6	1984@51	26.9	600 A A	
235/45R18	24000138	98V	BW	XL	10/32	8.00	7.50 - 9.00	9.3	26.3	1653@51	25.7	600 A A	
235/55R18	24000149	100V	BW	SL	10/32	7.50	6.50 - 8.50	9.6	28.1	1764@44	27.9	600 A A	
235/60R18	24000148	107V	BW	XL	10/32	7.00	6.50 - 8.50	9.4	29.1	2149@51	28.9	600 A A	
225/55R19	24000150	99V	BW	SL	10/32	7.00	6.00 - 8.00	9.2	28.8	1709@44	28.0	600 A A	
235/45R19	24000153	99V	BW	XL	10/32	8.00	7.50 - 9.00	9.3	27.4	1709@51	26.7	600 A A	
235/50R19	24000152	103V	BW	XL	10/32	7.50	6.50 - 8.50	9.6	28.3	1929@51	28.6	600 A A	
235/55R19	24000151	105V	BW	XL	10/32	7.50	6.50 - 8.50	9.6	29.2	2039@51	28.1	600 A A	

► Features Rim Protector

SA07 SPORT

PERFORMANCE TOURING · PASSENGER CAR / CUV

QUICK FACTS

- 69 Sizes · 16" - 22" Rim Diameters · Performance Touring
- 10/32 Tread Depth · Limited Treadwear Warranty



45K
MILE WARRANTY



ROAD HAZARD
PROGRAM

V-W-Y
SPEED RATING

460 A A
UTQG

Developed for today's sports-minded cars and CUV's, the **SA07** Performance Touring tire is an all-season high performer ready to enhance your driving experience. It has four wide circumferential grooves and tread blocks with cross siping to improve wet traction and promote even treadwear. The center rib provides a contact patch to promote stability and responsive handling for improved traction and cornering.



REDUCED NOISE



WET TRACTION



ALL-SEASON



IMPROVED TREAD LIFE

Symmetric all-season tread design simplify tire rotation options for better wear and tread life.



ENHANCED CONTROL AND STABILITY

Rigid, minimally siped, center rib enhances lateral stability and control through continuous tire-to-road contact.



INCREASED GRIP AND TRACTION

Cross-grain siping pattern increases traction by creating extra surface area for enhanced grip.



OPTIMIZED WET TRACTION

Four circumferential grooves optimize water evacuation for enhanced wet traction.



Wheel Diameter	Size	Item Number	Service Index	Sidewall	LR/PR	Tread Depth	Rim Width (Measured)	Rim Width (Approved)	Section Width	Overall Diameter	Max Load	Approximate Weight	UTQG
16"	195/45R16	24336004	84V	BW	XL	10/32	6.50	6.00 - 7.50	8.0	22.8	1102@51	17.7	460 A A
	225/50R16	24365010	92W	BW	SL	10/32	7.00	6.00 - 8.00	9.2	24.9	1389@44	21.0	460 A A
	205/40Z16	24870021	84W	BW	XL	10/32	7.50	7.00 - 8.00	8.3	23.5	1102@51	18.8	460 A A
	205/45Z16	24947006	88W	BW	XL	10/32	7.50	6.50 - 7.50	8.5	24.1	1235@51	20.7	460 A A
17"	215/40Z16	24875015	87W	BW	XL	10/32	7.50	7.00 - 8.50	8.6	23.8	1102@51	20.6	460 A A
	215/45Z16	24975012	91W	BW	XL	10/32	7.00	7.00 - 8.00	8.4	24.6	1356@51	21.8	460 A A
	225/45Z16	24977021	94W	BW	XL	10/32	7.50	7.00 - 8.50	8.9	25.0	1477@51	22.6	460 A A
	235/45Z16	24980014	97W	BW	XL	10/32	8.00	7.50 - 9.00	9.3	25.4	1609@51	24.2	460 A A
	245/40Z16	24081001	95W	BW	XL	10/32	8.50	8.00 - 9.50	9.8	24.7	1521@51	24.9	460 A A
	245/45Z16	24982009	95Y	BW	SL	10/32	8.00	7.50 - 9.00	9.6	25.7	1521@44	26.3	460 A A
	245/50R16	24375502	99V	BW	SL	10/32	7.50	7.00 - 8.50	10.0	26.7	1709@44	27.1	460 A A
	255/45Z16	24985003	98W	BW	SL	10/32	8.50	8.00 - 9.50	10.0	26.1	1653@44	27.8	460 A A
	215/35Z18	24030010	84W	BW	XL	10/32	7.50	7.00 - 8.50	8.6	23.9	1100@51	22.1	460 A A
	215/40Z18	24888005	89W	BW	XL	10/32	7.50	7.00 - 8.50	8.8	24.6	1279@51	21.2	460 A A
18"	215/45Z18	24970003	89W	BW	SL	10/32	7.00	7.00 - 8.00	8.4	25.6	1279@44	24.7	460 A A
	215/55R18	24495002	99V	BW	XL	10/32	7.00	6.00 - 7.50	8.9	27.3	1709@51	23.8	460 A A
	225/35Z18	24050007	87Y	BW	XL	10/32	8.00	7.50 - 9.00	10.0	25.0	1202@42	22.2	460 A A
	225/40Z18	24077016	92W	BW	XL	10/32	8.00	7.50 - 9.00	9.1	25.1	1389@51	23.2	460 A A
	225/45Z18	24990007	95W	BW	XL	10/32	7.50	7.00 - 8.50	8.9	25.9	1521@51	23.7	460 A A
	235/40Z18	24080022	95W	BW	XL	10/32	8.50	8.00 - 9.50	9.5	25.4	1521@51	24.0	460 A A
	235/50R18	24410005	101W	BW	XL	10/32	7.50	6.50 - 8.50	9.6	27.3	1819@51	30.3	460 A A
	245/35Z18	24055005	92Y	BW	XL	10/32	8.50	8.00 - 9.50	9.8	24.8	1389@51	23.8	460 A A
	245/40Z18	24082011	97Y	BW	XL	10/32	8.50	8.00 - 9.50	9.8	25.7	1609@51	26.9	460 A A
	245/45Z18	24995009	96Y	BW	SL	10/32	8.00	7.50 - 9.00	9.6	26.7	1565@44	28.0	460 A A
	245/50R18	24375004	100Y	BW	SL	10/32	7.50	7.00 - 8.50	10.0	27.7	1764@44	29.8	460 A A
	245/55R18	24374502	103W	BW	SL	10/32	7.50	7.00 - 8.50	10.0	28.6	1929@44	30.1	460 A A
	255/35Z18	24045013	94Y	BW	XL	10/32	9.00	8.50 - 10.00	10.2	25.0	1477@42	24.5	460 A A
	255/40Z18	24848006	99Y	BW	XL	10/32	9.00	8.50 - 10.00	10.2	26.0	1709@51	25.0	460 A A
	265/35Z18	24051015	97Y	BW	XL	10/32	9.50	9.00 - 10.50	10.7	25.3	1609@51	24.8	460 A A
	275/35Z18	24053005	99Y	BW	XL	10/32	9.50	9.00 - 11.00	10.7	25.5	1709@42	28.9	460 A A
19"	225/35Z19	24034008	88Y	BW	XL	10/32	8.00	7.50 - 9.00	9.1	25.2	1235@51	23.1	460 A A
	225/40Z19	24078003	93W	BW	XL	10/32	8.50	7.50 - 9.00	9.3	25.9	1433@51	23.9	460 A A
	225/45Z19	24853002	96Y	BW	XL	10/32	7.50	7.00 - 8.50	8.9	27.0	1565@51	23.7	460 A A
	235/35Z19	24052009	91W	BW	XL	10/32	8.50	8.00 - 9.50	9.5	25.5	1356@51	25.0	460 A A
	235/40Z19	24851003	96W	BW	XL	10/32	8.50	8.00 - 9.50	9.5	26.4	1565@51	24.6	460 A A
	245/35Z19	24054007	93Y	BW	XL	10/32	8.50	8.00 - 9.50	9.8	25.8	1433@51	24.7	460 A A
	245/40Z19	24083007	94Y	BW	SL	10/32	8.50	8.00 - 9.50	9.8	26.7	1477@44	29.3	460 A A
	245/45R19	24996008	98V	BW	SL	10/32	8.00	7.50 - 9.00	9.6	27.7	1653@44	28.0	460 A A
	245/50R19	24864001	105W	BW	XL	10/32	7.50	7.00 - 8.50	10.0	28.7	2039@51	29.9	460 A A
	255/35Z19	24049004	96W	BW	XL	10/32	9.00	8.50 - 10.00	10.2	26.0	1565@51	27.4	460 A A
	255/40Z19	24848002	100W	BW	XL	10/32	9.00	8.50 - 10.00	10.2	27.0	1764@51	30.1	460 A A
	255/45R19	24985501	100V	BW	SL	10/32	8.50	8.00 - 9.50	10.0	28.1	1764@44	30.0	460 A A
	265/35Z19	24026504	98Y	BW	XL	10/32	9.50	9.00 - 10.50	10.7	26.3	1653@51	26.1	460 A A
	275/35Z19	24062005	100Y	BW	XL	10/32	9.50	9.00 - 11.00	10.9	26.6	1764@51	29.1	460 A A
	275/40R19	24736007	101W	BW	SL	10/32	9.50	9.00 - 11.00	11.2	27.5	1819@44	30.3	460 A A
	20"	225/35Z20	24058010	90Y	BW	XL	10/32	8.00	7.50 - 9.00	9.1	26.2	1323@51	24.2
235/35Z20		24352007	92Y	BW	XL	10/32	8.50	8.00 - 9.50	9.5	26.5	1389@51	24.9	460 A A
245/30Z20		24532006	90Y	BW	XL	10/32	8.50	8.00 - 9.00	9.8	25.8	1323@51	25.7	460 A A
245/35Z20		24060006	95W	BW	XL	10/32	8.50	8.00 - 9.50	9.8	26.8	1521@51	28.7	460 A A
245/40Z20		24085004	99W	BW	XL	10/32	8.50	8.00 - 9.50	9.8	27.7	1709@51	28.4	460 A A
245/45Z20		24087006	99W	BW	SL	10/32	8.00	8.00 - 9.50	9.6	28.7	1709@44	30.0	460 A A
255/30Z20		24057009	92Y	BW	XL	10/32	9.00	8.50 - 9.50	10.2	26.1	1389@51	26.7	460 A A
255/35Z20		24065011	97Y	BW	XL	10/32	9.00	8.50 - 10.00	10.0	27.0	1609@51	26.4	460 A A
255/40Z20		24123400	101Y	BW	XL	10/32	9.00	8.50 - 10.00	10.2	27.9	1819@42	30.3	460 A A
255/45Z20		24984007	105W	BW	XL	10/32	8.50	8.00 - 9.50	10.0	29.1	2039@51	31.4	460 A A
265/35Z20		24079100	99Y	BW	XL	10/32	9.50	9.00 - 10.50	10.7	27.3	1709@51	29.3	460 A A
265/50R20		24652003	111V	BW	XL	10/32	8.50	7.50 - 9.50	10.9	30.5	2403@51	35.7	460 A A
275/30Z20		24059006	97Y	BW	XL	10/32	9.50	9.00 - 10.00	10.9	26.5	1611@51	28.6	460 A A
275/35Z20		24735005	102Y	BW	XL	10/32	9.50	9.00 - 11.00	10.9	27.6	1874@51	30.4	460 A A
275/40Z20		24084009	106W	BW	XL	10/32	9.50	9.00 - 11.00	10.9	28.7	2094@51	31.8	460 A A
285/30Z20		24061005	99Y	BW	XL	10/32	10.00	9.50 - 10.50	11.2	26.8	1709@42	30.9	460 A A
285/35Z20	24031002	100Y	BW	SL	10/32	10.00	9.50 - 11.00	11.4	27.9	1764@44	31.4	460 A A	
305/35Z20	24501001	104Y	BW	SL	10/32	11.00	10.00 - 12.00	12.3	28.4	1984@44	34.1	460 A A	
22"	235/30Z22	24051016	90W	BW	XL	10/32	8.50	8.50 - 8.50	9.5	27.6	1323@51	26.8	460 A A
	245/30Z22	24028006	92W	BW	XL	10/32	8.50	8.00 - 9.00	9.8	27.8	1389@51	27.7	460 A A
	255/30Z22	24057010	95W	BW	XL	10/32	9.00	8.50 - 9.50	10.2	28.1	1521@51	29.0	460 A A
	265/35Z22	24072004	102W	BW	XL	10/32	9.50	9.00 - 10.50	10.7	29.3	1874@51	31.4	460 A A
	265/40Z22	24022005	106W	BW	XL	10/32	9.50	9.00 - 10.50	10.7	30.4	2094@51	33.6	460 A A
295/30Z22	24076002	103W	BW	XL	10/32	10.50	10.00 - 11.00	11.9	29.0	1931@42	34.7	460 A A	

◆ No Rim Protector

SU318 RADIAL H/T

TOURING · CUV / SUV



QUICK FACTS

- 46 Sizes · 15" - 22" Rim Diameters · Touring
- ~12/32 Tread Depth · Limited Treadwear Warranty

50K
MILE WARRANTY



ROAD HAZARD
PROGRAM

T·H·V
SPEED RATING

500 A A
UTQG

Developed for everyday comfort and styling for your CUV and SUV, the **SU318** has a smooth and responsive ride. The innovative M+S design promotes excellent all-season traction, with lateral siping and four circumferential grooves promoting water evacuation to provide excellent grip and handling for confident, year-long performance.



REDUCED NOISE



WET TRACTION



ALL-SEASON



QUIET AND COMFORTABLE RIDE

Advanced CAD-designed block and siping pattern minimize road noise.




ENHANCED CORNERING AND HANDLING

Angled shoulder blocks improve grip and directional stability for optimal cornering and handling capabilities.



OPTIMIZED TRACTION

Serrated siping pattern enhances biting edges for superior grip and traction.



WET AND DRY PERFORMANCE

Intricate siping and quad-circumferential groove pattern optimizes tire-to-road contact for a variety of seasons.



Wheel Diameter	Size	Item Number	Service Index	Sidewall	LR/PR	Tread Depth	Rim Width (Measured)	Rim Width (Approved)	Section Width	Overall Diameter	Max Load	Approximate Weight	UTQG
15"	215/75R15	24745009	100T	BW	SL	11/32	6.00	5.50 - 7.00	8.5	27.7	1764@44	29.7	500 A A
	225/70R15	24250004	100T	BW	SL	11/32	6.50	6.00 - 7.50	9.0	27.4	1764@44	29.4	500 A A
	225/75R15	24750006	102T	BW	SL	11/32	6.00	6.00 - 7.00	8.8	28.3	1874@44	31.6	500 A A
	235/70R15	24252002	103T	BW	SL	12/32	7.00	6.00 - 8.00	9.4	28.0	1930@44	31.0	500 A A
	235/75R15	24760011	105T	BW	SL	11/32	6.50	6.00 - 7.00	9.3	28.9	2039@44	33.1	500 A A
16"	225/75R16	24751002	104T	BW	SL	11/32	6.00	6.00 - 7.00	8.8	29.3	1984@44	33.9	500 A A
	235/70R16	24265009	106T	BW	SL	11/32	7.00	6.00 - 7.50	9.4	29.0	2094@44	32.9	500 A A
	235/75R16	24761001	108T	BW	SL	11/32	6.50	6.00 - 8.00	9.3	29.8	2205@44	34.3	500 A A
	245/70R16	24268007	111T	BW	XL	12/32	7.00	6.50 - 7.50	9.8	29.5	2150@51	35.6	500 A A
	245/75R16	24768005	111T	BW	SL	12/32	7.00	6.50 - 8.00	9.8	30.5	2403@44	37.5	500 A A
	255/65R16	24585003	109T	BW	SL	12/32	7.50	7.00 - 9.00	10.2	29.1	2270@44	38.3	500 A A
	255/70R16	24270005	111T	BW	SL	12/32	7.50	6.50 - 8.00	10.2	30.1	2403@44	38.3	500 A A
17"	265/70R16	24272007	112T	BW	SL	12/32	8.00	7.00 - 8.50	10.7	30.6	2469@44	39.6	500 A A
	265/75R16	24773003	116T	BW	SL	12/32	7.50	7.00 - 8.00	10.5	31.7	2756@44	41.0	500 A A
	245/65R17	24552508	107T	BW	SL	12/32	7.00	7.00 - 8.00	9.8	29.5	2149@44	34.5	500 A A
	245/70R17	24552603	110T	BW	SL	12/32	8.00	6.50 - 8.00	9.8	29.5	2337@44	38.3	500 A A
	255/65R17	24626004	110H	BW	SL	12/32	8.50	7.00 - 9.00	10.2	30.1	2337@44	38.3	500 A A
	255/70R17	24629001	112T	BW	SL	12/32	8.50	6.50 - 8.50	10.2	31.1	2469@44	40.0	500 A A
	265/60R17	24370003	108T	BW	SL	12/32	8.00	7.00 - 9.50	10.7	29.5	2205@44	37.0	500 A A
	265/65R17	24689005	112T	BW	SL	12/32	8.00	7.50 - 9.50	10.7	30.6	2469@44	40.2	500 A A
	265/70R17	24689206	115T	BW	SL	12/32	8.00	7.00 - 8.50	10.7	31.7	2679@44	41.4	500 A A
	275/60R17	24689303	110T	BW	SL	12/32	8.00	7.50 - 9.50	11.0	30.0	2337@44	39.8	500 A A
18"	285/65R17	24207002	116H	BW	SL	12/32	8.50	8.00 - 10.00	11.5	31.6	2756@44	43.5	500 A A
	235/65R18	24658003	106H	BW	SL	11/32	7.00	6.50 - 8.50	9.4	30.0	2094@44	34.9	500 A A
	245/60R18	24376004	105T	BW	SL	12/32	7.00	7.00 - 8.50	9.8	29.6	2039@44	35.5	500 A A
	255/55R18	24995102	109V	BW	XL	12/32	8.00	7.00 - 9.00	10.4	29.0	2271@51	36.1	500 A A
	255/60R18	24609001	112V	BW	XL	12/32	8.50	7.00 - 9.00	10.2	30.0	2469@51	37.1	500 A A
	255/65R18	24627003	111T	BW	SL	12/32	7.50	7.00 - 9.00	10.2	31.1	2403@44	37.0	500 A A
	255/70R18	24499002	113T	BW	SL	12/32	7.50	6.50 - 8.50	10.2	32.1	2535@36	41.8	500 A A
	265/60R18	24583302	114V	BW	XL	12/32	8.00	7.50 - 9.50	10.7	30.5	2337@51	39.6	500 A A
	265/65R18	24651002	114T	BW	SL	12/32	8.00	7.50 - 9.50	10.7	31.5	2601@44	41.1	500 A A
	265/70R18	24890006	116T	BW	SL	12/32	8.00	7.00 - 9.00	10.7	32.6	2756@44	38.9	500 A A
19"	275/65R18	24531004	116T	BW	SL	12/32	8.00	7.50 - 9.00	11.0	32.1	2756@36	42.5	500 A A
	P245/55R19	24377003	103V	BW	SL	11/32	7.50	7.00 - 8.50	10.0	29.6	1929@44	34.0	500 A A
	255/50R19	24083009	107V	BW	XL	11/32	8.00	7.00 - 9.00	10.4	29.1	1929@51	32.6	500 A A
	255/55R19	24502102	111V	BW	XL	11/32	8.00	7.00 - 9.00	10.4	30.0	2403@42	33.8	500 A A
	255/60R19	24628002	109H	BW	SL	12/32	7.50	7.00 - 9.00	10.2	31.1	2271@44	36.4	500 A A
20"	235/55R20	24498003	102H	BW	SL	11/32	7.50	6.50 - 8.50	9.6	30.2	1874@44	33.0	500 A A
	245/50R20	24374005	102V	BW	SL	11/32	7.50	7.00 - 8.50	10.0	29.7	1874@44	33.8	500 A A
	P255/50R20	24502004	109V	BW	SL	11/32	8.00	7.00 - 9.00	10.4	30.1	2271@51	35.9	500 A A
	255/55R20	24503202	107H	BW	SL	11/32	8.00	7.00 - 9.00	10.4	31.0	2149@44	35.0	500 A A
	275/40R20	24084002	106V	BW	XL	11/32	9.50	9.00 - 11.00	10.9	28.7	1874@51	34.6	500 A A
	275/45R20	24910007	110V	BW	XL	11/32	9.00	8.50 - 10.50	10.7	29.8	2337@42	34.9	500 A A
22"	275/55R20	24660002	117V	BW	XL	12/32	8.50	7.50 - 9.50	11.2	31.9	2535@51	42.8	500 A A
	275/60R20	24466007	115H	BW	SL	12/32	8.00	7.50 - 9.50	11.0	33.0	2679@44	39.8	500 A A
	285/45R22	24459902	114H	BW	XL	11/32	9.50	9.00 - 10.50	11.2	32.1	2601@51	40.0	500 A A

◆ No Rim Protector

SL309 RADIAL A/P

A/P · LIGHT TRUCK

QUICK FACTS

- 10 Sizes · 16" - 18" Rim Diameters · All-Purpose
- ~16/32 Tread Depth · Limited Treadwear Warranty



40K
MILE WARRANTY



**ROAD HAZARD
PROGRAM**



SPEED RATING

The **SL309** is an all-purpose, heavy duty performer for your light truck application. The M+S all-season tread design incorporates open shoulders and circumferential grooves that help dispel water and debris, while lateral-siped tread blocks improve traction performance on paved, gravel, and dirt roads. Robust steel-belted construction provide optimal treadlife along with heavy duty construction for load hauling.



REDUCED NOISE



WET TRACTION



DURABILITY



OPTIMIZED COMFORTABLE AND QUIET RIDE

Variable pitch tread reduces road noise for a smoother, quieter ride.



VARIABLE DEPTH SIPING

Open shoulder design enhances quicker water evacuation for better wet traction.



IMPROVED GRIP AND TRACTION

Staggered tread blocks improve grip and traction with an enhanced tire-to-road contact.



CONFIDENT HANDLING

Circumferential ribs improve highway stability, lateral traction, and steering response.



Wheel Diameter	Size	Item Number	Service Index	Side-wall	LR / PR	Tread Depth	Rim Width (Measured)	Rim Width (Approved)	Section Width	Overall Diameter	Max Load (Single)	Max Load (Dual)	Approximate Weight
16"	LT215/85R16	22860014	115/112Q	BW	E/10	11/32	6.00	5.50 - 7.00	8.5	30.4	2680@80	2470@80	39.8
	LT225/75R16	22265015	115/112Q	BW	E/10	12/32	6.00	6.00 - 7.00	8.8	30.5	2680@80	2470@80	39.2
	LT235/85R16	22270033	120/116Q	BW	E/10	13/32	6.50	6.00 - 7.50	9.3	31.7	3042@80	2778@80	46.3
	LT245/75R16	22275034	120/116Q	BW	E/10	13/32	7.00	6.50 - 8.00	9.8	30.5	3042@80	2778@80	43.8
	LT265/75R16	22279030	123/120Q	BW	E/10	13/32	7.50	7.00 - 8.00	10.5	31.7	3415@80	3085@80	49.3
17"	LT235/80R17	22275603	120/117Q	BW	E/10	14/32	6.50	6.00 - 7.50	9.3	31.8	3085@80	2835@80	46.7
	LT245/70R17	22269015	119/116Q	BW	E/10	16/32	7.00	6.50 - 8.00	9.8	30.6	3000@80	2755@80	49.2
	LT245/75R17	22275503	121/118Q	BW	E/10	14/32	7.00	6.50 - 7.50	9.8	31.5	3195@80	2910@80	46.9
	LT265/70R17	22810023	123/120Q	BW	E/10	15/32	8.00	7.00 - 8.50	10.7	31.7	3415@80	3085@80	53.4
18"	LT275/65R18	22687002	123/120Q	BW	E/10	14/32	8.00	7.50 - 9.00	11.0	32.1	3415@80	3085@80	52.0

SL369 RADIAL A/T

A/T · LIGHT TRUCK



QUICK FACTS

- 45 Sizes · 15" - 20" Rim Diameters · All-Terrain
- ~16/32 Tread Depth · Limited Treadwear Warranty

40K
MILE WARRANTY



**ROAD HAZARD
PROGRAM**

Q·R·S·T
SPEED RATING

500 A A
UTQG

The tough **SL369** All-Terrain is designed to tackle off-road and rocky conditions, head-on. Wide, deep grooves with switchback tread blocks provide optimal off-road traction during inclement conditions, while the tread pattern allows for a quiet and comfortable on-road drive. The SL369 is the go-to tire that offers a great balance of both on and off-road truck performance.



OFF-ROAD



WET-TRACTION



DURABILITY



WHITE NOISE PRODUCTION

Variable pitch tread integrated with unique siping patterns reduce road harmonics.




RESPONSIVE BRAKING AND GRIP

Improved siping pattern and rigid tread blocks enhance braking response.



OPTIMIZED ON AND OFF-ROAD TRACTION

Aggressive tread block designed for maximum on and off-road traction.



IMPROVED WET AND DRY TRACTION

Angled siping pattern improves wet traction by providing extra grip on wet surfaces while edged shoulder blocks enhanced dry traction.



Wheel Diameter	Size	Item Number	Service Index	Sidewall	LR/PR	Tread Depth	Rim Width (Measured)	Rim Width (Approved)	Section Width	Overall Diameter	Max Load (Single)	Max Load (Dual)	Approximate Weight	UTQG
15"	235/75R15	24760013	109S	BW	XL	12/32	6.50	6.00 - 8.00	9.3	28.9	2271@51	-	34.1	500 A A
	31X10.50R15LT	22285019	109Q	BW	C/6	16/32	8.50	7.00 - 9.00	10.6	30.5	2270@50	-	46.7	-
	LT235/75R15	22870001	104/101Q	BW	C/6	14/32	6.50	6.00 - 8.00	9.3	28.9	1985@50	1820@50	39.2	-
	P235/70R16	24265013	106S	BW	SL	12/32	7.00	6.00 - 8.00	9.4	29.0	2094@36	-	34.5	500 A A
16"	235/75R16	24761002	112S	BW	XL	12/32	6.50	6.00 - 8.00	9.3	29.8	2469@51	-	34.5	500 A A
	245/70R16	24268009	111S	BW	XL	13/32	7.00	6.50 - 8.00	9.8	29.5	2403@51	-	38.0	500 A A
	245/75R16	24768007	111S	BW	SL	13/32	7.00	6.50 - 8.00	9.8	30.5	2403@44	-	39.5	500 A A
	255/70R16	24270009	111T	BW	SL	13/32	7.50	6.50 - 8.50	10.2	30.1	2403@36	-	40.2	500 A A
	265/70R16	24272009	112S	BW	SL	13/32	8.00	7.00 - 9.00	10.7	30.6	2469@44	-	41.6	500 A A
	265/75R16	24773005	116S	BW	SL	13/32	7.50	7.00 - 9.00	10.5	31.7	2756@44	-	43.8	500 A A
	LT215/85R16	22860015	115/112Q	BW	E/10	14/32	6.00	5.50 - 7.00	8.5	30.4	2680@80	2470@80	42.8	-
	LT225/75R16	22112001	115/112Q	BW	E/10	14/32	6.00	6.00 - 7.50	8.8	29.3	2680@80	2470@80	42.5	-
	LT235/85R16	22270034	120/116Q	BW	E/10	16/32	6.50	6.00 - 7.50	9.3	31.7	3042@80	2778@80	49.1	-
	LT245/75R16	22275035	120/116Q	BW	E/10	16/32	7.00	6.50 - 8.00	9.8	30.5	3042@80	2778@80	48.6	-
	LT265/75R16	22279031	123/120Q	BW	E/10	15/32	7.50	7.00 - 9.00	10.5	31.7	3415@80	3085@80	51.6	-
	LT285/75R16	22789019	126/123Q	BW	E/10	16/32	8.00	7.50 - 9.50	11.3	32.8	3750@80	3415@80	58.9	-
	LT315/75R16	22790004	127/124R	BW	E/10	16/32	8.50	8.00 - 10.50	12.3	34.6	3858@65	3527@65	63.3	-
17"	235/65R17	24657010	104S	BW	SL	12/32	7.00	7.00 - 8.50	9.4	29.1	1984@44	-	34.3	500 A A
	235/75R17	22021000	109T	BW	SL	12/32	6.50	6.00 - 8.00	9.3	30.9	2271@44	-	35.2	500 A A
	245/65R17	24552510	107S	BW	SL	13/32	7.00	7.00 - 8.50	9.8	29.5	2150@44	-	38.1	500 A A
	255/70R17	24629002	112T	BW	SL	13/32	7.50	6.50 - 8.50	10.2	31.1	2469@44	-	39.7	500 A A
	255/75R17	22130003	115T	BW	SL	13/32	7.00	6.50 - 8.50	10.0	32.0	2679@44	-	41.5	500 A A
	265/65R17	24689008	112S	BW	SL	13/32	8.00	8.00 - 9.50	10.7	30.6	2469@44	-	41.6	500 A A
	P265/70R17	24689211	115T	BW	SL	13/32	8.00	7.00 - 9.00	10.7	31.7	2679@44	-	43.6	500 A A
	285/70R17	24695001	117T	BW	SL	13/32	8.50	7.50 - 9.50	11.5	32.8	2833@36	-	47.5	500 A A
	35X12.50R17LT	22229010	125Q	BW	E/10	16/32	10.00	8.50 - 10.50	12.5	34.5	3640@65	-	64.4	-
	LT235/80R17	22275604	120/117Q	BW	E/10	16/32	6.50	6.00 - 7.50	9.3	31.8	3085@80	2835@80	49.1	-
	LT245/70R17	22269005	119/116Q	BW	E/10	16/32	7.00	6.50 - 8.00	9.8	30.6	3000@80	2755@80	48.6	-
	LT245/75R17	22275504	121/118Q	BW	E/10	16/32	7.00	6.50 - 8.00	9.8	31.5	3195@80	2910@80	48.1	-
	LT265/70R17	22810027	123/120Q	BW	E/10	16/32	8.00	7.00 - 8.50	10.7	31.7	2415@80	3085@80	53.4	-
LT285/70R17	22688021	126/123Q	BW	E/10	16/32	8.50	7.50 - 9.00	11.5	32.8	3750@80	3415@80	66.0	-	
LT315/70R17	22801008	126/123R	BW	E/10	16/32	9.50	8.00 - 11.00	12.7	34.4	3750@65	3415@65	63.3	-	
18"	265/60R18	24583309	110T	BW	SL	13/32	8.00	8.00 - 9.50	10.7	30.5	2337@44	-	40.6	500 A A
	265/65R18	24651006	114T	BW	SL	13/32	8.00	8.00 - 9.50	10.7	31.5	2601@44	-	42.6	500 A A
	275/65R18	24531005	116T	BW	SL	12/32	8.00	8.00 - 9.50	11.0	32.1	2756@36	-	43.7	500 A A
	LT265/70R18	22815005	124/121R	BW	E/10	16/32	8.00	7.00 - 9.00	10.7	32.6	3525@80	3195@80	58.4	-
	LT275/65R18	22687003	123/120Q	BW	E/10	16/32	8.00	8.00 - 9.50	11.0	32.1	3415@80	3085@80	54.9	-
	LT275/70R18	22797007	125/122S	BW	E/10	16/32	8.00	7.00 - 9.00	11.0	33.2	3640@80	3305@80	56.4	-
	LT285/65R18	22402002	125/122R	BW	E/10	16/32	8.50	8.50 - 10.00	11.8	33.1	3640@80	3305@80	61.3	-
20"	265/50R20	24652007	111T	BW	XL	13/32	8.50	8.00 - 9.50	10.9	30.5	2403@51	-	41.6	500 A A
	275/55R20	24660005	113S	BW	SL	12/32	8.50	8.00 - 9.50	11.2	31.9	2535@36	-	41.6	500 A A
	275/60R20	24466004	115T	BW	SL	12/32	8.00	8.00 - 9.50	11.0	33.0	2679@36	-	43.4	500 A A
	LT275/65R20	22689305	126/123S	BW	E/10	16/32	8.00	8.00 - 9.50	11.0	34.1	3748@80	3417@80	58.6	-
	LT285/55R20	22401507	122/119R	BW	E/10	16/32	9.00	8.50 - 10.00	11.7	32.4	3305@80	3000@80	63.3	-
LT305/55R20	22789701	121/118R	BW	E/10	16/32	9.50	9.00 - 11.00	12.4	33.2	3197@65	2910@65	66.2	-	

SL376 RADIAL M/T

M/T - LIGHT TRUCK

QUICK FACTS

- 27 Sizes · 15" - 26" Rim Diameters
- Mud-Terrain · 19/32 Tread Depth



Q-R
SPEED RATING

UP TO **F/12**
LOAD RANGE

UP TO **40"**
OVERALL DIAMETER

Engineered for extreme off-road performance without compromising on-road comfort, the **SL376** is built for adventure. Robust tread blocks deliver superior traction, while the optimized void ratio ensures confident handling across diverse terrain. Step-down supports enhance stability, and offset shoulder blocks provide extra grip in mud, rugged trails, and snowy conditions. The aggressive upper sidewall shields against sharp rocks and adds traction, while integrated stone ejectors help prevent debris buildup. The SL376 is ready to conquer any challenge, on or off the road.



OFF-ROAD



WET-TRACTION




DURABILITY




RUGGED & RIGID TREAD BLOCKS

Delivers excellent off-road traction without sacrificing on-road performance.



OPTIMAL VOID RATIO

Engineered to effectively navigate through all types of road conditions.



STEP-DOWN SUPPORT

Enhance stability and handling while providing protection against stone drilling.



AGGRESSIVE UPPER SIDEWALL

Greater protection from sharp rocks and provide additional off-road traction.



Wheel Diameter	Size	Item Number	Service Index	Side-wall	LR/PR	Tread Depth	Rim Width (Measured)	Rim Width (Approved)	Section Width	Overall Diameter	Max Load (Single)	Max Load (Dual)	Approximate Weight
15"	30X9.50R15LT	22280011	104Q	BW	C/6	19/32	7.50	6.00 - 8.50	9.4	29.5	1985@50	-	42.4
	31X10.50R15LT	22285034	109Q	BW	C/6	19/32	8.50	7.00 - 9.00	10.6	30.7	2270@50	-	48.1
	32X11.50R15LT	22232004	113Q	BW	C/6	19/32	9.00	7.50 - 10.00	11.4	31.5	2535@50	-	51.9
	33X12.50R15LT	22228005	108Q	BW	C/6	19/32	10.00	8.00 - 10.50	12.5	32.5	2205@35	-	59.2
	35X12.50R15LT	22228504	113Q	BW	C/6	19/32	10.00	8.00 - 10.50	12.5	34.5	2535@35	-	63.4
	LT235/75R15	22270511	104/101Q	BW	C/6	19/32	6.50	6.00 - 8.00	9.3	29.1	1985@50	1820@50	42.1
16"	LT235/85R16	22270054	120/116Q	BW	E/10	19/32	6.50	6.00 - 7.50	9.3	31.7	3042@80	2778@80	46.8
	LT245/75R16	22275055	120/116Q	BW	E/10	19/32	7.00	6.50 - 8.00	9.8	30.5	3042@80	2778@80	47.3
	LT265/75R16	22279051	123/120Q	BW	E/10	19/32	7.50	7.00 - 9.00	10.5	31.9	3415@80	3085@80	54.1
	LT285/75R16	222789026	126/123Q	BW	E/10	19/32	8.00	7.50 - 9.50	11.3	33.1	3750@80	3415@80	58.9
	LT315/75R16	22790009	127/124R	BW	E/10	19/32	8.50	8.00 - 10.50	12.3	34.6	3860@65	3525@65	63.4
17"	35X12.50R17LT	22229012	125Q	BW	E/10	19/32	10.00	8.50 - 11.00	12.5	34.5	3640@65	-	66.7
	LT235/80R17	22275612	120/117Q	BW	E/10	19/32	6.50	6.00 - 8.00	9.3	31.8	3085@80	2835@80	47.7
	LT245/75R17	22275515	121/118Q	BW	E/10	19/32	7.00	6.50 - 8.00	9.8	31.5	3195@80	2910@80	50.1
	LT255/75R17	22130005	111/108Q	BW	C/6	19/32	7.00	6.50 - 8.50	10.0	32.0	2405@50	2205@50	47.4
	LT265/70R17	22810028	123/120Q	BW	E/10	19/32	8.00	7.00 - 8.50	10.7	31.7	3415@80	3085@80	56.3
	LT285/70R17	22688023	126/123Q	BW	E/10	19/32	8.50	7.50 - 9.00	11.5	32.8	3750@80	3415@80	58.2
18"	35X12.50R18LT	22229256	123Q	BW	E/10	19/32	10.00	8.50 - 11.00	12.5	34.8	3415@65	-	67.6
	LT275/65R18	22272510	123/120Q	BW	E/10	19/32	8.00	8.00 - 9.50	11.0	32.1	3415@80	3085@80	60.3
	LT275/70R18	22797013	125/122Q	BW	E/10	19/32	8.00	7.00 - 9.00	11.0	33.2	3640@80	3305@80	62.5
20"	35X12.50R20LT	22229508	121Q	BW	E/10	19/32	10.00	8.50 - 11.00	12.5	34.5	3195@65	-	68.2
	LT275/65R20	22689314	126/123Q	BW	E/10	19/32	8.00	8.00 - 9.50	11.0	34.3	3415@80	3750@80	65.2
	LT305/55R20	22789709	125/122Q	BW	F/12	19/32	9.50	9.00 - 11.00	12.4	33.5	3305@80	3640@80	69.2
22"	35X12.50R22LT	22229702	117Q	BW	E/10	19/32	10.00	8.50 - 11.00	12.5	34.8	2835@65	-	74.1
	37X13.50R22LT	22371302	123Q	BW	E/10	19/32	11.00	9.50 - 12.00	13.6	36.5	3415@65	-	83.7
24"	40X15.50R24LT	22455800	128Q	BW	E/10	19/32	12.50	11.00 - 14.00	15.6	39.8	3970@65	-	98.7
26"	40X15.50R26LT	22480200	126Q	BW	E/10	19/32	12.50	11.00 - 14.00	15.6	39.5	3750@65	-	102.4

SC328

COMMERCIAL VAN

QUICK FACTS

· 1 Size · 16" Rim Diameter



R

SPEED RATING

The **SC328**, redefines durability and performance. Engineered for heavy-duty driving, the SC328 boasts superior compounds and advanced load-carrying designs. Its gripping edges, circumferential traction ribs, and robust shoulders deliver unparalleled traction, while sturdy sidewalls increase the maximum load capacity and combat wear damage. Built for heavier loads, and commercial use, the Westlake SC328 features a ribbed shoulder design for stability and reduced wear, deep zig-zag grooves for rapid water evacuation, and an all-season pattern and enhanced tread compound for exceptional performance in any weather. Elevate your driving experience with the Westlake SC328.



ALL-SEASON



WET-TRACTION



DURABILITY



HEAVY DUTY TIRES

Designed for higher PSI, heavier loads, and commercial use.



DURABLE RIBBED SHOULDER DESIGN

Provides greater stability and reduces irregular wear.



DEEP ZIG-ZAG GROOVES

Promote rapid water evacuation and improves traction and stability even under heavy loads.



ALL-SEASON

Pattern design and tread compound enhanced for seasonal conditions.



Wheel Diameter	Size	Item Number	Service Index	Side-wall	LR/PR	Tread Depth	Rim Width (Measured)	Rim Width (Approved)	Section Width	Overall Diameter	Max Load (Single)	Max Load (Dual)	Approximate Weight
16"	235/65R16C	23000001	121/119R	BW	E/10	12/32	7.00	6.50 - 8.50	9.4	28.0	3195@83	3000@83	39.7

SIZE MATRIX

WESTLAKE TIRES PRODUCT LINEUP



WHEEL DIAMETER	SIZE	RP218	SAO7	SU318	SL369	SL376	WHEEL DIAMETER	SIZE	RP218	SAO7	SU318	SL309	SL369	SL376	
13"	155/80R13	✓					16"	235/65R16	✓						
	175/70R13	✓						235/70R16					✓		
14"	175/65R14	✓						235/75R16				✓	✓	✓	
	175/70R14	✓						245/70R16				✓	✓	✓	
	185/60R14	✓						245/75R16				✓	✓	✓	
	185/65R14	✓						255/65R16				✓	✓	✓	
	185/70R14	✓						255/70R16				✓	✓	✓	
	195/70R14	✓						265/70R16				✓	✓	✓	
15"	205/70R14	✓						265/75R16				✓	✓	✓	
	175/65R15	✓						LT215/85R16					✓	✓	✓
	185/55R15	✓					LT225/75R16					✓	✓	✓	
	185/60R15	✓					LT235/85R16					✓	✓	✓	
	185/65R15	✓					LT245/75R16					✓	✓	✓	
	195/50R15	✓					LT265/75R16					✓	✓	✓	
	195/55R15	✓					LT285/75R16						✓	✓	
	195/60R15	✓					LT315/75R16							✓	
	195/65R15	✓					205/40R17		✓						
	205/60R15	✓					205/45R17		✓	✓					
	205/65R15	✓					205/50R17	✓		✓					
	205/70R15	✓					215/40R17			✓					
	215/60R15	✓					215/45R17			✓					
	215/65R15	✓					215/50R17	✓		✓					
	215/70R15	✓					215/55R17	✓		✓					
	215/75R15	✓			✓		215/60R17	✓		✓					
	225/70R15			✓	✓		215/65R17	✓		✓					
	225/75R15			✓	✓		225/45R17		✓						
235/70R15			✓	✓	✓	225/50R17		✓							
235/75R15			✓	✓		225/55R17	✓		✓						
30X9.50R15LT						225/60R17	✓		✓						
31X10.50R15LT					✓	225/65R17	✓		✓						
32X11.50R15LT						235/45R17		✓		✓					
33X12.50R15LT						235/50R17	✓		✓						
35X12.50R15LT						235/55R17	✓		✓						
LT235/75R15					✓	235/60R17	✓		✓						
16"	185/55R16	✓					235/65R17	✓					✓		
	195/45R16		✓				235/75R17					✓			
	195/50R16	✓					245/40R17					✓			
	195/55R16	✓					245/45R17				✓	✓			
	205/50R16	✓					245/50R17				✓	✓			
	205/55R16	✓					245/65R17				✓	✓			
	205/60R16	✓					245/70R17				✓	✓			
	205/65R16	✓					255/45R17		✓						
	205/70R16	✓					255/65R17				✓	✓			
	215/55R16	✓					255/70R17				✓	✓			
	215/60R16	✓					255/75R17				✓	✓			
	215/65R16	✓					265/60R17				✓	✓			
	215/70R16	✓					265/65R17				✓	✓			
	225/50R16			✓			265/70R17				✓	✓			
	225/55R16	✓		✓			275/60R17				✓	✓			
	225/60R16	✓					285/65R17				✓	✓			
	225/65R16	✓					285/70R17				✓	✓			
	225/70R16	✓					35X12.50R17LT						✓	✓	
225/75R16	✓			✓		LT235/80R17					✓	✓	✓		
235/60R16	✓					LT245/70R17					✓	✓	✓		



WHEEL DIAMETER	SIZE	RP218	SA07	SU318	SL309	SL369	SL376
17"	LT245/75R17				✓	✓	✓✓✓
	LT255/75R17					✓	✓✓✓
	LT265/70R17				✓	✓	✓✓✓
	LT285/70R17					✓	✓✓
	LT315/70R17					✓	✓
18"	215/35R18		✓✓				
	215/40R18		✓✓				
	215/45R18		✓✓				
	215/55R18		✓✓				
	225/35R18		✓✓				
	225/40R18		✓✓				
	225/45R18		✓✓				
	225/50R18	✓✓					
	225/55R18	✓✓					
	225/60R18	✓✓					
	235/40R18		✓				
	235/45R18	✓					
	235/50R18	✓					
	235/55R18	✓✓					
	235/60R18	✓✓					
	235/65R18				✓		
	245/35R18			✓			
	245/40R18			✓✓			
	245/45R18			✓✓			
	245/50R18			✓✓			
	245/55R18			✓✓			
	245/60R18			✓	✓		
	255/35R18			✓			
	255/40R18			✓			
	255/45R18			✓			
	255/50R18			✓			
	255/55R18			✓	✓		
	255/60R18			✓	✓		
	255/65R18			✓	✓		
	255/70R18			✓	✓		
	265/35R18			✓	✓		
	265/60R18				✓	✓	
265/65R18				✓	✓		
265/70R18				✓	✓		
275/35R18			✓				
275/65R18				✓			
35X12.50R18LT						✓	
LT265/70R18						✓	
LT275/65R18					✓	✓	
LT275/70R18					✓	✓	
LT285/65R18					✓	✓	
19"	225/35R19		✓				
	225/40R19		✓				
	225/45R19		✓				
	225/55R19	✓					
	235/35R19		✓				
	235/40R19		✓				
	235/45R19		✓				
	235/50R19		✓				
	235/55R19		✓				
	245/35R19			✓			
	245/40R19			✓			
	245/45R19			✓			
	245/50R19			✓			
	245/55R19			✓			

WHEEL DIAMETER	SIZE	RP218	SA07	SU318	SL369	SL376	
19"	245/40R19		✓				
	245/45R19		✓				
	245/50R19		✓				
	245/55R19		✓	✓			
	255/35R19		✓				
	255/40R19		✓				
	255/45R19		✓				
	255/50R19		✓	✓			
	255/55R19		✓	✓			
	255/60R19		✓	✓			
	265/35R19		✓				
	275/35R19		✓				
	275/40R19		✓				
	225/35R20		✓				
	235/35R20		✓				
235/55R20		✓	✓				
245/30R20		✓					
245/35R20		✓					
245/40R20		✓					
245/45R20		✓					
245/50R20		✓					
255/30R20		✓					
255/35R20		✓					
255/40R20		✓					
255/45R20		✓					
255/50R20		✓		✓			
255/55R20		✓		✓			
265/35R20		✓			✓		
265/50R20		✓			✓		
275/30R20		✓					
275/35R20		✓					
275/40R20		✓					
275/45R20		✓		✓			
275/55R20		✓		✓			
275/60R20		✓		✓			
285/30R20		✓					
285/35R20		✓					
305/35R20		✓					
35X12.50R20LT						✓	
LT275/65R20						✓	
LT285/55R20						✓	
LT305/55R20						✓	
22"	235/30R22		✓				
	245/30R22		✓				
	255/30R22		✓				
	265/35R22		✓				
	265/40R22		✓				
	285/45R22		✓	✓			
	295/30R22		✓				
	35X12.50R22LT						✓
	37X13.50R22LT						✓
	24"	40X15.50R24LT					✓
26"	40X15.50R26LT					✓	

STANDARD LIMITED WARRANTY

Every tire and wheel supplied by Tireco is warranted to be free from defects in materials and workmanship subject to the terms, conditions, and limitations as stated below. If our examination of a warrantable product determines that the product has failed due to a defect in materials or workmanship, we will make a reasonable allowance toward the purchase of a new product at current prices or other adjustment within our discretion. Adjustments will be made on a pro-rata basis determined by the amount of usage or service received by the product and will be based on the most recent purchase price by an authorized Tireco dealer (proof of purchase is required).

TERMS, CONDITIONS, AND LIMITATIONS

Any product, no matter how well constructed, may fail in service or become unserviceable due to conditions beyond the control of the manufacturer. Under no circumstance is this Standard Limited Warranty a representation that a tire, tube, or wheel failure cannot occur.

WHAT IS COVERED:

This Standard Limited Warranty is only applicable to products sold in and used on vehicles registered & operated in the United States, U.S. Territories, Canada, and Mexico. In addition, this Standard Limited Warranty is applicable only to the original purchaser of the product, and is not transferable. The costs of mounting, balancing, and other associated services as well as any applicable Federal, State or Local taxes are not covered by this Standard Limited Warranty.

WHAT IS NOT COVERED:

This Standard Limited Warranty does not cover and Tireco will not adjust any of our products against road hazards (unless the product is specifically included in our Road Hazard program and subject to the Road Hazard Limited Warranty terms and conditions), including, but not limited to: cuts, punctures (whether repairable or not), snags, bruises, tears, impact breaks, etc. Products are also not warranted if damaged due to misuse, including, but not limited to, improper installation or mounting, misapplication, improper repair, overloading, improper inflation, excessive speed, racing, spinning, drifting, unintended off-road use, stone drilling, improper use of chains, use of non-approved or non-standard rims (as determined by the Tire and Rim Association), continued operation while severely under-inflated, misalignment or imbalance of wheels/rims, defective brakes or shock absorbers, abuse, accident or collision, willful damage, oil or chemical action, improper storage, fire or other excessive heat, vandalism, and water or other material entrapped inside the product.

SPECIFIC TIRE LIMITATIONS AND EXCLUSIONS

- Tire adjustments will be based on the remaining tread depth. Tires worn to 2/32" tread depth or to the treadwear indicator bars are deemed to have served their full useful tread life and are not adjustable for any reason.
- Tires returned for out-of-round or ride disturbance conditions within the first 2/32" of treadwear will be credited for 100% of their value based on the average purchase price by an authorized Tireco dealer for the last six months. Tires returned for out of round beyond the first 2/32 of wear will not be considered for adjustment. Off-road, Agriculture, and Trailer tires are not eligible for out-of-round or ride disturbance consideration.
- Tires that have been marked or branded to note special classifications such as "B" (appearance blemish) may not be considered for adjustment at Tireco's sole discretion.
- Tires that have been marked or branded with an "NA" (nonadjustable) are specifically excluded from this Standard Limited Warranty.
- For tires designed for and used on all classes of recreational vehicles, equipment trailers, horse trailers, cargo trailers and all other trailers; Tireco may require a certified weight ticket for any warranty consideration. Specialty Trailer (ST size designation tires) are specifically limited to a warranty of five (5) years from date of manufacture and any allowance made will be based on our Manufacturer's Suggested Retail Price (MSRP)
- Loss of time, or use, inconvenience, or any incidental or consequential damage are not covered by this warranty, subject to applicable state law.
- Tires which have been retreaded (other than those specifically mentioned in our Limited Casing Warranty) or altered in any way are not warranted.
- Tires that do not have a Department of Transportation (DOT) number; tires that fail due to the addition of aftermarket materials (tire fill, sealant, balancer, etc.); tires that have been modified by notching, buffing or cutting; tires returned for weather/ozone cracking after two (2) years from date of purchase; tires with production dates six (6) years and older.

SPECIFIC WHEEL LIMITATIONS AND EXCLUSIONS

- Cosmetic defects caused by weathering as well as used, reconditioned or blemished wheels are specifically excluded from this Standard Limited Warranty.
- Chrome plating and clear coat finishes are warranted against peeling, cracking, and other cosmetic flaws for a period of one (1) year from date of purchase.
- New wheels returned without all of the original packaging material in good condition including the original box will be charged a 15% restocking fee.

HOW TO FILE A CLAIM:

Each step of the following procedures must be completed in order to qualify for any credit provided by this Standard Limited Warranty:

1. The dealer must contact the Tireco Consumer Relations Department to receive a Return Merchandise Number (RMA) to start the warranty claim process.
 - a. rma@tireco.com
 - b. 1-800-937-9433
2. The Tireco authorized dealer must use the Warranty Claim Form provided by Tireco for any adjustments to be considered for credit. The Claim Form must be filled in completely (Tire size, Tread pattern, DOT, Remaining tread, etc.) for each tire being returned.
3. The Consumer Relations Representative will request tire(s) to be sent to one of Tireco's Adjustment Centers at our expense for inspection. Shipping instructions along with an RMA number will be provided.
4. The dealer must send the completed Claim Form and all other documents to the Adjustment Center.
5. Upon receipt of documents and tires, the appropriate Tireco Representative will complete the inspection.
6. If the tire(s) is deemed adjustable, the authorized Tireco dealer will be notified and will be issued a credit after which the tire will be destroyed by Tireco.
7. If the tire(s) is not adjustable and does not meet the limited Standard Warranty requirements, the authorized Tireco dealer will receive a letter of notification with an explanation. If the tire(s) was requested by the dealer to be returned, the non-adjustable tire(s) will be returned at the expense of the dealer. Any tire that the dealer leaves with Tireco will be destroyed without further notice.
8. No credit shall be given until a completed warranty claim form and all documents related to the claim are received by Tireco and the tire is found to be adjustable.
9. Any form that is illegible or incomplete may be returned to the dealer for completion and will delay the application process.
10. For any questions or if you need assistance in filling out the forms, please call Tireco Consumer Relations Department at 1-800-937-9433 or rma@tireco.com.

PLEASE NOTE:

All tires/wheels returned to Tireco for warranty consideration are subject to inspection. Tires/wheels that are found to not meet the warranty criteria (adjustable) will be disposed of at the time of inspection unless the tires/wheels have been previously requested to be returned. All tires/wheels returned to the dealer/customer will be done at the dealer's/customer's expense.

TO ASK QUESTIONS, REQUEST INFORMATION OR FILE A CLAIM:

Contact our warranty professionals at 1-800-937-9433 or via email at rma@tireco.com. No claim will be considered unless submitted in accordance with our standard claim procedures. Claim forms and all warranty related forms can be found on our website www.tireco.com. All product returns must be accompanied by a completed Return Material Authorization (RMA) form and number. Products submitted without prior authorization will not be processed and are subject to freight chargeback.

YOUR RIGHTS UNDER STATE LAW:

All implied warranties, including any warranty of merchantability or fitness for a particular purpose, are expressly limited to the duration of this Standard Limited Warranty. All obligations or liabilities for indirect, incidental or consequential damages are hereby excluded to the extent permitted by law, including economic loss, loss of profit, loss of use of vehicle, loss of time, inconvenience, personal injury or death. Some states/provinces do not allow limitations on how long an implied warranty lasts, or the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusions may not apply. This Standard Limited Warranty gives the customer legal rights that may vary from state/province to state/province. This Standard Limited Warranty, the Standard Limited Mileage Warranty, and the Road Hazard Program are the only express warranties applicable to items sold by Tireco and supersede the terms of any previous warranty.

STANDARD LIMITED MILEAGE & ROAD HAZARD WARRANTY

WHAT IS COVERED:

In addition to our Standard Limited Warranty, some Westlake tires are warranted for mileage warranty during a limit of five years from the installation date. This Standard Limited Mileage Warranty only applies to select new Passenger & Light Truck tire lines listed below:

40K MILE WARRANTY	45K MILE WARRANTY	50K MILE WARRANTY	55K MILE WARRANTY
SL309 RADIAL A/P SL369 RADIAL A/T	SA07 SPORT	SU318 RADIAL H/T	FORAY RP218

LIMITED MILEAGE WARRANTY:

If within five (5) years from the date of installation, the tire wears evenly across the tread down to the tread wear indicators (2/32nds of an inch of tread remaining) before providing the minimum warranted miles of service as indicated by the vehicle odometer, a credit will be issued toward the purchase of a new tire on a pro-rated basis to the actual mileage received. The mileage received will be based on the current vehicle mileage on the odometer when the tires wear to the tread wear indicators, compared to the vehicle mileage at the time of the original new tire installation, which must be listed on the original tire invoice and the new tire invoice.

Tires which wear out evenly before delivering the warranted mileage will be replaced on a pro-rated basis only if:

- You are the original purchaser of the tires and you still own the vehicle on which they were originally installed. The tires must have only been used on that vehicle.
- The tires have been rotated and inspected by any authorized tire dealer every 5,000 miles, and the Mounting and Rotation service record has been fully completed and signed by the dealer (the form is available at www.westlaketireusa.com). Improper or incorrectly performed maintenance or repair that causes damage to the tires may void this warranty.
- There is no more than one puncture repair in the tread area of the tire. The puncture repair must contain a plug and innerliner patch, been properly repaired by a trained technician, and the tire does not exhibit any conditions indicating that it was operated for an extended period of time at low to no air pressure.
- The tires were originally registered online at www.westlaketireusa.com.
- The completed service record form, Tire Installation Information Form, and the original invoices are presented to the authorized Westlake tire dealer at the time of the mileage warranty claim. These forms can be found on our website at www.westlaketireusa.com or contact our Consumer Relations Department at 1-800-937-9433.

HOW TO GET SERVICE:

Each step of the following procedures must be completed in order to qualify for any credit provided by this Standard Limited Mileage Warranty:

1. The dealer/customer must contact the Tireco Consumer Relations Department to receive a Return Merchandise Number (RMA) to start the mileage warranty claim process at rma@tireco.com or 1-800-937-9433.
2. The dealer/customer must use the Warranty Claim Form provided by Tireco for any adjustments to be considered for credit. The Claim Form must be filled in completely (Tire size, Tread pattern, DOT, Remaining tread, etc).
3. To obtain mileage proration adjustments the dealer/customer must have completed the Tire Installation Form (found at www.westlaketireusa.com) and provide proof of original purchase for the claim tires(s) that states the vehicle mileage at the time of the original installation.
4. Dealer/customer must obtain proof that the tires have been rotated every 5,000 miles and complete and sign Tireco's Mounting and Rotation Service Record (For Mileage Warranty) Form found at www.westlaketireusa.com
5. The Consumer Relations Representative will request tire(s) to be sent to one of Tireco's Adjustment Centers at our expense for inspection. Shipping instructions along with an RMA number will be provided.
6. The dealer/customer must send the completed Claim Form and all other documents for the mileage warranty with Tires to the Adjustment Center.
7. Upon receipt of documents and tires, the appropriate Tireco Representative will complete the inspection.
8. If the tire(s) is adjustable, the dealer will be notified and will be issued a credit after which the tire will be destroyed by Tireco.
9. If the tire(s) is not adjustable and does not meet the limited mileage requirements, the dealer will receive a letter of notification with an explanation. If the tire(s) was requested by the dealer to be returned, the non-adjustable tire(s) will be returned at the expense of the dealer. Any tire that the dealer leaves with Tireco will be destroyed without further notice.
10. No credit shall be given until a completed warranty claim form and all documents related to the claim are received by Tireco and the tire is found to be adjustable.
11. Any form that is illegible or incomplete may be returned to the dealer/customer for completion and will delay the application process.
12. For any questions or if you need assistance in filling out the forms, please call Tireco consumer relations department 1-800-937-9433 or email us at rma@tireco.com.

ROAD HAZARD WARRANTY

Westlake is offering a Road Hazard warranty on the following eligible Westlake passenger and light truck tires:

- FORAY RP218
- SA07 SPORT
- SU318 RADIAL H/T
- SL309 RADIAL A/P
- SL369 RADIAL A/T

Tire must be listed in eligible products for Road Hazard.

If the tire becomes unserviceable due to road hazard damage within the first year from the date of purchase, or within the first 2/32nds of the original usable tread, whichever comes first, the eligible Westlake tire will be replaced with an identical or comparable tire at no charge.

Tires must have been purchased through an authorized Westlake dealer and must be returned for replacement to that same dealer.

On-line sales are not eligible.

Taxes, mounting, balancing and service charges on the replacement tires are not included.

WHAT IS COVERED:

- Damage due to cuts, punctures, snags, bruises, tears, impact breaks, etc.
- Products sold in and used on vehicles registered & operated in the United States, U.S. Territories, and Canada.
- Road Hazard Warranty is only available to the original purchaser of the product, and is not transferable.

WHAT IS NOT COVERED:

Damage caused by:

- Fire
- Theft
- Vandalism
- Chemical corrosion
- Accident
- Off-road use
- Stone Drilling
- Alteration
- Improper inflation or improper installation
- Mechanical failures (e.g., failed shocks, struts, alignment, balancing, or similar failure) or interference of tire with vehicle.
- Improper mounting/dismounting practices.
- Abuse, misuse, or neglect.
- Repairable punctures (Nail or other debris punctures in the tread area), repair conforming to U.S. Tire Manufacturers Association standards, are not covered under this warranty.

DISCLAIMER

LIMITED MILEAGE AND ROAD HAZARD WARRANTY IS IN ADDITION TO THE STANDARD LIMITED WARRANTY FOR ALL WESTLAKE TIRES. FOR A COMPLETE LIST OF ALL WARRANTIES, PLEASE VISIT WESTLAKETIREUSA.COM.

WEST LAKE TIRES®

500 W. 190TH STREET, SUITE 600
GARDENA, CA 90248

CUSTOMER SERVICE
TOLL FREE
800.227.8925

ONLINE SERVICES
tireco.com
customerservice@tireco.com

TELEPHONE
310.767.7990



@westlaketires



@westlaketires



westlaketireusa.com

